



Australasian Building Solutions Pty Ltd
ABN: 78 117 403 924

ABS - TROWEL GRADE

MATERIAL SPECIFICATION

Description: Modified elastomeric bitumen emulsion formulated specifically as a trowel grade product to waterproof seal cracks, holes, crevices and construction extrusions. Cold applied Single component Brush/squeegee application forms a flexible membrane ideally applied prior to ABS- Spray Grade application.

Appearance: Dark **Brown** cures to **Black Viscous Liquid**

Solids Content: 63 - 68%

Viscosity, Brookfield #5, 20rpm@ 25°C 30,000 - 50,000

Specific Gravity: 1.0 approx.

pH value: 10 - 12

Packaging: 20 Litre pails.

Storage: Store out of direct sunlight above 5 Degrees C.

Regulatory: ABS-Trowel Grade is not classed as a dangerous nor hazardous transportation material.

ABS- Trowel Grade is used in conjunction with protective coatings to seal cracks, holes, pipe penetration pass- throughs, in preventing water/air leaks + corrosion damage from the elements.

Application: **ABS-Trowel Grade is cold applied by trowel or squeegee using between 1.6 to 4.8 Litres per m², best applied in thin 1mm coats curing by evaporation. Use of a reinforcing fabric is recommended when sealing cracks or joins. Application temperature is recommended @ above 15 Degrees C. The product fully cures within 24 Hours @ 20 C and should be applied to a dry surface free of dirt grease debris or oils and is not recommended to be applied prior to any expected heavy rain.**

Limitations: **ABS-Trowel Grade is Mildly Alkaline, ensure that appropriate safety apparel worn and safety precautions adopted and do not apply to wet surfaces or some surface base coats such as coal tar which are unsuitable to ABS Trowel Grade. Consult MSDS for further data.**

Caution: **For Industrial use only. Keep out of reach of Children. Avoid storage below 5 degrees C and please consult material safety data sheet prior to use of ABS-Trowel Grade.**

Preparer's Contact Details:

Australasian Building Solutions Pty Ltd
ABN 78 117 403 924

Tech support **Mobile +61 0418 295025**
PO Box 1677 Surfers Paradise, Qld., Australia
4217 **Ph: +61 7 567 70243 **Fax:** +61 7**
56770243

This information sheet is based upon available data and on an Information Only basis. Australasian Bldg Solutions makes no warranties, guarantees or conditions, expressed or implied, regarding the accuracy of the data or its use thereof. Aust Bldg Solutions Pty Ltd will not be liable for any damages arising from the use of information or product described on this data sheet.